


技术数据

波长L[mm]	12.5
轴材质	不锈钢
外壳材料	镀锌膜
电气连接	接插件, M12 × 1
轴轴向负载能力	20 N
轴径向负载能力	40 N
环境条件	
工作温度	-40...+85 °C
抗震动性(EN 60068-2-6)	300 m/s ² , 10...2000 Hz
抗冲击性(EN 60068-2-27)	2500 m/s ² , 6 ms
防护等级	IP67
防护等级 (轴型 / 轴套)	IP67


附件

RA-BC-20-06-06 100048777




带铝制轮毂的波纹管联轴器Ø 20 mm ; d1 = 6 mm , d2 = 6 mm

RA-BC-20-06-08 100048778




带铝制轮毂的波纹管联轴器Ø 20 mm ; d1 = 6 mm , d2 = 8 mm

RA-BC-20-06-10 100048779




带铝制轮毂的波纹管联轴器Ø 20 mm ; d1 = 6 mm , d2 = 10 mm

RA-BC-E-20-06-06 100048785




不锈钢波纹管联轴器Ø 20 mm ; d1 = 6 mm , d2 = 6 mm

RA-BC-E-20-06-10 100048786




不锈钢波纹管联轴器Ø 20 mm ; d1 = 6 mm , d2 = 10 mm

RA-SDC-30-06-10 100048791




弹性盘联轴器Ø 30 mm , d1 = 6 mm , d2 = 10 mm

RA-SDC-30-06-06 100048790




弹性盘联轴器Ø 30 mm , d1 = 6 mm , d2 = 6 mm

RA-HC-25-06-06 100048794



铝制螺旋联轴器Ø 25 mm ; d1 = 6 mm , d2 = 6 mm

RA-HC-25-06-10 100048795



铝制螺旋联轴器Ø 25 mm ; d1 = 6 mm , d2 = 10 mm

附件

尺寸图	型号	货号	
	E-RKC 8T-264-2	U-04781	线缆连接，孔头 M12、直角；8 针（双绞线），屏蔽，线缆长度：2 m；护套材质:PVC, 黑色; cULus 认证; 其他线路长度应可订货，详情参看see www.turck.com

