

## IO-Link Starterkit IO-Link Starterkit

Type	IO-Link Starterkit
ID	100012813


Included in delivery	<p>Carrying case, black/yellow □ Bottom lining, black, 248 x 182 x 33 mm, account assigned □ Cover profile foam, black, 248 x 182 x 21 mm 1:2 □ Plug-in power supply, 24 VDC 0.5 A Type 512692 — NA with M8 female connector □ 8-GB USB stick with software set □ IO-Link master TBENS2-4IOL (6814024) □ Ethernet cable PSGS4M-RJ45S-4414-1M (6933004) □ Connection cable RKC4T-2-RSC4T/TXL (6625604) □ I/O hub TBILS4-8DXP (100002596) □ Inductive sensor BI10U-M18-IOL6X2-H1141 (1644875) □ Ultrasonic sensor RU40U-M18M-AP8X2-H1151 (1610094) □ Indicator light K50L2RGBKQ (3802158)</p>
----------------------	---



- Complete set including IO-Link master, IO-Link sensors, I/O hub, parameterization software and accessories
- Includes 230 VAC/24 VDC power supply



## Function accessories

Type code	Ident no.		Dimension drawing
RU40U-M18M-AP8X2-H1151/P0001	100032174	Ultrasonic sensor; cylindrical, threaded barrel; 18 mm; nickel-plated brass	 <p>M18 x 1  <i>24/4</i>  <i>20 Nm</i>      LED      48      15      M12 x 1</p>