


Analog Signal Isolator 1-channel IM12-AO01-1I-1I-H0/24VDC/K71



The 1-channel IM12-AO01-1I-1I-H0/24VDC/K71 signal isolator is designed to transmit the normalized current signal galvanically isolated 1:1. In addition to the analog signal, digital HART communication signals can also be transmitted bidirectionally. Typical applications are for example the control of I/P converters or indicators.

The green LED indicates operational readiness. The device can detect a wire break or short circuit on the field side, the input then switches to a high impedance state. A fault in the input circuit causes the red LED to flash according to NE44.

The device complies with the requirements of NE21. It is equipped with removable screw terminals.


The device is equipped with removable screw terminals.

- Output circuit monitored for wire break and short circuit
- Complete galvanic isolation
- HART transparent
- Removable screw terminals



Dimensions

Type	IM12-AO01-1I-1I-H0/24VDC/K71
ID	100051439
Operating voltage U_s	10...30 VDC
Power dissipation, typical	≤ 1.31 W
Input current	4...20 mA
Reference temperature	23 °C
Output circuits	
Output current	4...20 mA
Load resistance current output	≤ 0.8 k Ω
Minimum load	≥ 50 Ω
Short-circuit	At a load resistance of < 30 Ω , the input current is < 500 μ A
Wire break	at a load resistance of > 30 k Ω the input current is < 500 μ A
Response characteristic	
Rise time (10...90 %)	≤ 10 ms
Fall time (90...10 %)	≤ 10 ms
Measuring accuracy (including linearity, hysteresis and repeatability)	≤ 0.05 % of full scale
Temperature drift	≤ 0.002 % of full scale/K
Galvanic isolation	
Input 1 to output 1	375 V peak value acc. to EN 60079-11
Input 1 to supply	375 V peak value acc. to EN 60079-11
A1A supply voltage	300 V RMS acc. to EN 50178 and EN 61010-1



Mechanical data		
Protection class	IP20	
Flammability class acc. to UL 94	V-0	
Dimensions	120 x 12.5 x 117 mm	
Weight	166 g	
Mounting instructions	DIN rail (NS35)	
Housing material	Plastic, Polycarbonate/ABS	
Electrical connection	Removable screw terminals, 2-pin	
Terminal cross-section	0.2...2.5 mm ² (AWG: 24...14)	
Tightening torque	0.5 Nm	
Tightening torque	4.43 LBS-Inch	
Environmental conditions	Operating height	Up to 2000 m above sea level
	Pollution degree	II
	Surge/Overvoltage category	II (EN 61010-1)
	Standards used	
	Voltage resistance and insulation	
		EN 50178
		EN 61010-1
		EN 50155
		GL VI-7-2
	Shock	
		EN 61373 class B
		EN 50155
		GL VI-7-2
		EN 60068-2-6
		EN 60068-2-27
	Temperature	
		EN 60068-2-1 Ad
		EN 50155
		GL VI-7-2
		EN 60068-2-2 Bd
		EN 60068-2-1
	Air humidity	
		EN 60068-2-38
	EMC	
		EN 50155
		GL VI-7-2
		NE21
		EN 61326-1
		EN 61326-3-1
		EN 61000-4-2
		EN 61000-4-3
		EN 61000-4-4
		EN 61000-4-5
		EN 61000-4-6
		EN 61000-4-11
		EN 61000-4-29
		EN 55011
		EN 55016
		EN 50121-3-2
		EN 61000-6-2

Accessories

Type code	Ident no.		Dimension drawing
IMX12-SC-2X-4BK	7580940	Screw terminals for IM(X)12 modules; included in delivery: 4 pcs. of 2-pin black terminals	
IMX12-CC-2X-4BK	7580942	Spring terminals for IM(X)12 modules; included in delivery: 4 pcs. black terminals, 2-pin	