TL50BLY1ALSQ
LED Signal Light – Tower Light



Technical data

Type	TL50BLY1ALSQ
ID	3028459
Signal and display data	
Purpose	LED indicator light
Function	Tower light
Light type	Yellow, rotating
Dimmable	No
Features of color 1	Yellow, Rotating, 15 lm
Acoustic signal	Continuous tone, 94 dB
Electrical data	
Operating voltage U_B	12…30 VDC
DC rated operating current I_e	≤ 125 mA
Operating voltage U_B	21…27 VAC
AC rated operational current	≤ 100 mA
Max. current consumption per color	125 mA
Max. current consumption of beeper	35 mA
Input type	Bipolar (PNP/NPN)
Response time typical	< 1 ms
Mechanical data	
Cascadable	No
Design	Smooth barrel, TL50BL
Dimensions	Ø 50 x 119.2 mm
Housing material	Plastic, ABS, Black
Window material	Polycarbonate, clear
Electrical connection	Connector, M12 × 1, PVC
Number of cores	4
Ambient temperature	-20…+50 °C

Features

- Black plastic housing
- Protection class IP67
- EMI and RFI immune
- Monochrome: Yellow rotating (COL 1)
- Operating voltage: 12…30 VDC or 24 VAC with 45 mA per LED color
- Inputs: PNP/NPN
- Beeper: Sealed, continuous tone max. 94 dB

Wiring diagram



Functional principle

The rugged multifunction TL50 beacon is available in many variations and is easily mounted. Each signal tower can be assembled from a maximum of four varicolored LEDs, with or without a beeper. You can also choose from three different lighting functions (steady, rotating, flashing). The lighting function is indicated in the type code after the color (no number: steady; 1: rotating; 2: flashing). Clearly visible status displays for indoor and outdoor applications. The wiring diagram shows a PNP pin assignment.
5 colors are available, blue (B), green (G), red (R), yellow (Y) and white (W), which specify the light sequence from bottom to top in the type designation of the tower light. Example: TL50GYRQ, designates the colors green, yellow and red from bottom to top.

TL50BLY1ALSQ| 04-03-2025 12-50 | Technical modifications reserved

Technical data

Relative humidity	0…95 %
Protection class	IP67
Tests/approvals	
Approvals	CE, UL listed

Accessories

SMB30A	3032723

Mounting bracket, rectangular, stainless steel, for sensors with 30mm thread



SMB30FA	3074005

Montagewinkel; Werkstoff VA 1.4401



SMB30SC	3052521

Mounting bracket, PBT black, for sensors with 30 mm thread, rotatable



Accessories

Dimension drawing	Type	ID	
	RKC4.4T-2/TEL	6625013	Connection cable, M12 female connector, straight, 4-pin, cable length: 2 m, jacket material: PVC, black; cULus approval

	WKC4.4T-2/TEL	6625025	Connection cable, M12 female connector, angled, 4-pin, cable length: 2 m, jacket material: PVC, black; cULus approval



TL50BLY1ALSQ| 04-03-2025 12-50 | Technical modifications reserved