

K100PBLZGYRAQ

LED Signal Light




Technical data

Type	K100PBLZGYRAQ
ID	3813069
Signal and display data	
Purpose	LED indicator light
Light type	Green Yellow Red
Aperture angle degree	360 °
LED service life (L70)	42000 h
Dimmable	No
Features of color 1	Green, 360 lm
Features of color 2	Yellow, 525 lm
Features of color 3	Red, 155 lm
Acoustic signal	Key adjustable, 101 dB
Electrical data	
Operating voltage U _B	100...240 VAC
AC rated operational current	≤ 100 mA
Mechanical data	
Cascadable	No
Design	Dome
Dimensions	Ø 118.5 x 173.2 mm
Housing material	Plastic, PC
Electrical connection	Connector, Single 1/2 in. NPT
with motion switch	no
Ambient temperature	-40...+60 °C
Storage temperature	-40...+70 °C
Relative humidity	90 %

Features

- All-round LED display
- Mechanical screw-in thread M36 × 2.0
- Protection class IP66
- Colors: Green (COL 1)/Yellow (COL 2)/Red (COL 3)
- Male connector, 5-pin

Wiring diagram



Functional principle

These indicator lights have color LEDs, depending on their type designation. Four input signals can be used to control up to three light colors and to activate the optional beeper. With the Pro Editor software, these lights can be assigned user-defined animations in the advanced settings and the functionality of the beeper can be adjusted. The major advantage of these LEDs is the color fidelity and luminance. The wiring diagram shows a PNP pin assignment.

Technical data

Protection class	IP66
Tests/approvals	
Approvals	CE, UL listed

Accessories

LMB36RA	3813539	SA-M36E12	3813537
SA-M36SOP	3813538		

Accessories

Dimension drawing	Type	ID
	MQAC2-530	3032718
	MQAC2-515	3032715
	MQAC2-506	3032713

Accessories

Dimension drawing	Type	ID	
	MQDC-506-USB	3803770	USB serial converter, for parameterizing PRO indicator lights or sensors via PC, female connector, M12 × 1, 5-pin to plug, USB type A, length 0.7 m, can be extended to a maximum of 30 m, supplies the connected device with 20 V, supports Windows 7 (driver required) and Windows 10

